# B\_

### Tulle

#### **Textured Collection: Broadloom & Rug**

On its own a thread has little strength, but when woven with others new potential emerges. The transformation of a single thread into a new material with its own properties reminds us to seek people with whom we can work to unlock new and unexpected possibilities within ourselves, and others.

#### **Extended Specifications**

Use Classification: Medium / General Commercial – 32 (EN 1307)

Construction: Level Cut Loop (LCL)

Recycled Content: Yarn – Stainproof SDX Eco (certain colours)

Yarn Type: Stainproof SDX (Solution Dyed Nylon - 6)

Yarn Mass:  $\pm 900 \text{ (g/m}^2) \mid \pm 26,54 \text{ (oz/yd}^2\text{) (ISO 8543)}$ 

Pile Height: ± 6.5 (mm) | ± 0,26 (in) (ISO 8543)

Stitch Rate: 40 (per 10cm) | 10,16 (per 1in)

Total Thickness: ± 9 (mm) | ± 0,35 (in) (ISO 8543)

Total Mass:  $\pm 1860 (g/m^2) | \pm 54,86 (oz/yd^2) (ISO 8543)$ 

Standard Size (Broadloom): 4 (m) | 157,48 (in)

Standard Backing: FusionBac



## B\_

## Tulle

**Textured Collection: Broadloom & Rug** 

### **Extended Specifications**

Machine Gauge: 1/10"

Pattern Repeat (lxw):  $\pm$  68 × 67 cm

Fire Classification: 3 (SANS 10177-4) Cfl-s1 (EN 13501-1) (ISO 9239)

Class 1 (ASTM E 648-08)

Colour Fastness To: Light > 6 (NF EN ISO 105-B02)

Water 4 – 5 (ISO 105-E01)
Dry Rubbing 4 – 5 (ISO 105-X12)
Wet Rubbing 4 – 5 (ISO 105-X12)

Electrostatic Propensity: ≤ 2 kV (EN 14041) / (ISO 6356)

Sound Absorption: 0,25 aw (EN ISO 354)
Sound Insulation: 27 dB (EN ISO 10140)

Thermal Resistance: 0,1201 m².K/W (ISO 8302)

VOC Tested: (ASTM D5116)
Castor Chair Suitability: (NF EN 985)

Staircase Suitability: (EN 1963) / (NF EN ISO 12951)

Warranty: 15 Year (Broadloom) 1 Year (Rug)

Guarantee: 5 Year (Broadloom) 1 Year (Rug)



# B




### Tulle


#### **Textured Collection: Broadloom & Rug**















(Broadloom)











Commercial



Heating



















#### **Bill of Quantities**

- Belgotex's TEXTURED collection is available as 1.6 × 2.4m/2 × 3m/2.4 × 3.4m/3 × 4m/0.8 × 3m rugs and as 4m wide General/Medium Commercial ±9mm (total thickness) FusionBac broadloom, manufactured from Stainproof SDX and Stainproof SDX ECO.
- · This product is to be laid in accordance with the SANS 10186 fitting code of practice.
- Belgotex recommends the use of carpet protector mats where castor wheels are used.
- 15 year warranty and 5 year guarantee for broadloom.
- 1 year warranty and 1 year guarantee for rugs.
- · Made in South Africa.
- · GreenTag Level A Gold Rated Certification.

\*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd. © BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.